





BLANKA ANGOLO CERAMIC



BLANKA ANGOLO CERAMIC
Blanco

BLANKA ANGOLO CERAMIC
Negro

BLANKA ANGOLO CERAMIC
Nieve

BLANKA ANGOLO PL CERAMIC

PL = Top connection

PRODUCT INFORMATION:

Thermal energy:	72,7 kWh,	PL: 74,2 kWh
Energy efficiency:	87 %,	PL: 88 %
CO%:	0,09 %,	PL: 0,09 %
Heat storage capacity:		
100 %	after 8,2 hours,	PL: after 8,6 hours
50 %	after 26,9 hours,	PL: after 28,2 hours
25 %	after 45,2 hours,	PL: after 47,4 hours

PRODUCT NUMBERS:

Product	Product number	Weight kg	Height mm
BLANKA ANGOLO CERAMIC	3KTC	1915	1831
BLANKA ANGOLO PL CERAMIC	3KTPC	1995	1831

NEEDED FOR ASSEMBLY:

* Mortar 1 x 25 kg (not included in NunnaUuni delivery)

PRODUCT INFORMATION

	BAKING OVEN / BAKING SPACE		FIREWOOD			FLUE CALCULATION VALUES ⁽¹⁾				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Width [mm]	Depth [mm]	Length fireplace / cooker [cm]	Max amount of wood [kg]	Length baking oven [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø (min.)	Temperature °C
Blanka Angolo Ceramic	-	-	33	20	-	203	-12	17	160	310
Blanka Angolo PL Ceramic	-	-	33	20	-	176	-12	17	180	310

FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]				FLUE CONNECTION MEASUREMENTS [mm]			INCOMING AIR			
	approx. 150x150	approx. 150x200	approx. 150x300	round Ø	[A]	[B]	[C]	Incoming air pipe location L [mm]	Replacement air unit	HRT	Burning air approx. m³/h
Blanka Angolo Ceramic	-	x	x	160-210	150-180	250	350	662	-	920006	35 - 50
Blanka Angolo PL Ceramic	-	-	-	180	-	-	-	662	-	920006	35 - 50

SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	According to EN 15250			
	Behind	On the sides	Top	Front
Blanka Angolo Ceramic	50	300	200	1000
Blanka Angolo PL Ceramic	50	300	200	1000

¹⁾ The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards. It is recommendable to contact chimney sweeper beforehand.

NOTES!

The recommended minimum flue height is 5 m. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue. In the picture you can see the Finnish version.

Country- and region-specific regulations must be adhered to when installing the fireplace

