

PRODUCT INFORMATION:

Thermal energy: 56,2 kWh, **PL: 56 kWh**, PL fc: 54,9 kWh

Energy efficiency: 82 %, **PL: 85 %**, PL fc: 79 %

CO%: 0,08 %, **PL: 0,08 %**, PL fc: 0,07 %

Heat storage capacity:

100% after 6,8 hours, **PL: after 6,6 hours**, PL fc: 5,4 h

50% after 22,5 hours, **PL: after 28,9 hours**, PL fc: 20,8 h


25% after 36,4 hours, **PL: after 49,5 hours**, PL fc: 35,7 h

PRODUCT NUMBER:


Product	Product number	Weight kg	Height mm
JOYA	2T	1500	1536
JOYA-2	2T-2	1560	1536
JOYA-3	2T-3	1565	1536
JOYA PL	2TP	1890	1536
JOYA PL FULL CIRCULATION	2TPK	1460	1536

NEEDED FOR ASSEMBLY:


* Mortar 1 x 25 kg (not included in NunnaUuni delivery)




JOYA




JOYA PL



JOYA PL FULL CIRCULATION



JOYA-2



JOYA-3

PL = Top connection

PRODUCT INFORMATION

	BAKING OVEN / BAKING SPACE		FIREWOOD			FLUE CALCULATION VALUES (1)				MAX. FLUE TEMPERATURE IN SECURITY TEST
	Width [mm]	Depth [mm]	Length fireplace / cooker [cm]	Max amount of wood [kg]	Length baking oven [cm]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø	Temperature °C
Joya	-	-	33	16	-	261	-12	17	160	362
Joya PL	-	-	33	16	-	219	-12	21	180	320
Joya PL full circul.	-	-	33	16	-	258	-12,1	21	180	397

FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]				FLUE CONNECTION MEASUREMENTS [mm]			INCOMING AIR			
	approx. 150x150	approx. 150x200	approx. 150x300	round Ø	[A]	[B]	[C]	Incoming air pipe location L [mm]	Replacement air unit	HRT	Burning air approx. m³/h
Joya	x	x	x	160-210	150-180	250	350	370	-	920006	35 - 50
Joya PL	-	-	-	180	-	-	-	514	-	920006	35 - 50
Joya PL full circul.	-	-	-	180	-	-	-	370	-	920006	35 - 50

SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	According to EN 15250			
	Behind	On the sides	Top	Front
Joya	50	150	200	1000
Joya PL	50	150	200	1000
Joya PL full circul.	50	150	200	1000

1) The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards. It is recommendable to contact chimney sweeper beforehand.

NOTES!

The recommended minimum flue height is 5 m with Ø180 mm. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is always recommended for a flue connection or flue. In the picture you can see the Finnish version.

Country- and region-specific regulations must be adhered to when installing the fireplace

