DECLARATION OF PERFORMANCE (DOP)

	NO. 90583600-CPR-20220912	
1.	Product Type:	Freestanding stove Scan 83
2.	Type, batch or serial number:	Scan 83 series (Scan 83-1, Scan 83-2, Scan 83-5, Scan 83-6, Scan 83-7, Scan 83-8)
3.	Intended use of the product:	Heat distribution/room heating Without hot water supply Fuel type: Wood
4.	Name and Address of the manufacturer:	Scan A/S Damsbovej 1 5492 Vissenbjerg
5.	Contact address:	No relevance
6.	AVCP System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR, Annex V	System 3
7.	Notified body: Test report no:	DTI NB-No 1235 300-ELAB-2611-EN
8.	Declared performance	333 22.13 2322 21.1
0.	Harmonized technical specification	EN 13240:2001/A2:2004/AC:2007
	Essential characteristics	Performance
	Figure 6.1 Described to fine	
	Fire safety Reaction to fire Distance to combustible materials Risk of burning fuel falling out	A1 Minimum distances in mm: Rear: 100 Sides: 550 Front: 1100 NPD
	Distance to combustible materials	Minimum distances in mm: Rear: 100 Sides: 550 Front: 1100
_	Distance to combustible materials Risk of burning fuel falling out	Minimum distances in mm: Rear: 100 Sides: 550 Front: 1100 NPD CO [979 mg/Nm³] NOx [95 mg/Nm³] OGC [56 mg/Nm³]
-	Distance to combustible materials Risk of burning fuel falling out Emission of combustion products	Minimum distances in mm: Rear: 100 Sides: 550 Front: 1100 NPD CO [979 mg/Nm³] NOx [95 mg/Nm³] OGC [56 mg/Nm³] Dust [22 mg/Nm³]
-	Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature	Minimum distances in mm: Rear: 100 Sides: 550 Front: 1100 NPD CO [979 mg/Nm³] NOx [95 mg/Nm³] OGC [56 mg/Nm³] Dust [22 mg/Nm³] Pass
	Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety	Minimum distances in mm: Rear: 100 Sides: 550 Front: 1100 NPD CO [979 mg/Nm³] NOx [95 mg/Nm³] OGC [56 mg/Nm³] Dust [22 mg/Nm³] Pass -
	Distance to combustible materials Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety Cleanability	Minimum distances in mm: Rear: 100 Sides: 550 Front: 1100 NPD CO [979 mg/Nm³] NOx [95 mg/Nm³] OGC [56 mg/Nm³] Dust [22 mg/Nm³] Pass - Pass
	Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety Cleanability Maximum water operating pressure	Minimum distances in mm: Rear: 100 Sides: 550 Front: 1100 NPD CO [979 mg/Nm³] NOx [95 mg/Nm³] OGC [56 mg/Nm³] Dust [22 mg/Nm³] Pass - Pass -
	Risk of burning fuel falling out Emission of combustion products Surface temperature Electrical safety Cleanability Maximum water operating pressure Flue gas temperature at nominal heat output [EN]	Minimum distances in mm: Rear: 100 Sides: 550 Front: 1100 NPD CO [979 mg/Nm³] NOx [95 mg/Nm³] OGC [56 mg/Nm³] Dust [22 mg/Nm³] Pass - Pass - T [236°C]

DECLARATION:

The performance of the product identified in points 1 and 2 in conformity with the declared performance in point 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed on behalf of the manufacturer:

Brian Steen Ørum (CEO)

Vissenbjerg, 12.09.2022 (Place and date of issue) SCAN

