



Product Type:	Poomheaters fired	l hy solid fuel
	Roomheaters fired by solid fuel	
Type, batch or serial number:	Jøtul FS 175 - I520	
Intended use of the product:		ng solid fuel without water sup
Name and Address of the manufacturer:	Jøtul AS	
	Postboks 1411, 1602 Fredrikstad, Norway	
	Tel.: +47 69 35 90	00
	E-mail: post@jotul	l.no
AVCP:	System 3	
System(s) of assessment and verification of constancy op performance (AVCP) of the construction product as set out in CPR. Annex V		
Notified body:	Danish Technological Institute	
NB-No:	NB-No 1235	
Test report no:	300-ELAB-2189-EN	I
Declared performance:		
Harmonized technical specification	EN 13240:2001/A2	2:2004/AC:2007
Fuel	Wood	
Essential characteristics	Performance	
Fire safety		
Reaction to fire	A1	
Distance to combustible materials	Minimum distance	es, in mm
	Rear =	50
	Sides =	250
	Height of ceiling	700
	See also the installation instructions	
Risk of burning fuel falling out	No	
Emission of combustion products	CO	[0,07 %]
	NOx	[54 mg/m3]
	OGC	[60 mgC/m3]
Surface temperature	PM Pass	[14 mg/m3]
Electrical safety	-	
Cleanability	Pass	
Maximum water operating pressure	-	
Flue gas temperature at nominal heat output	T [305°C]	
Mechanical resistance (to carry a chimney/flue)	NPD	
Thermal output		
Normal heat output	7 kW	
Room heating output	- kW	
Water heating output	-*kW	
Energy efficiency	η [77%]	

This declaration of performance is issued under the sole responsibility of the manufacturer.			
Signed on behalf	of the manufacturer:		
Tom J.			
R&D			
(Name and functi	on)		
Fredrikstad	April 6, 2016	Jon of Berglind	

The performance of the product in conformity with the declared performance.

April 6, 2016

Declaration:

(Place and date of issue)