


DEKO 7L UNO



DEKO 7R UNO

PRODUCT INFORMATION:

Nominal heat output:	8,0 kW
Energy efficiency:	80,1%
CO%:	0,09 %

PRODUCT NUMBERS:


Product	Product number	Weight kg	Height mm
DEKO 7L UNO	708280-1	680	1508
DEKO 7R UNO	708290-1	680	1508

PRODUCT INFORMATION


	FIREWOOD		FLUE CALCULATION VALUES ⁽¹⁾			
	Length [cm]	Max amount of wood [kg/h]	Flue gas temperature [°C]	Min. flue draught [Pa]	Mass flow [g/s]	Flue connection Ø (min.)
Deko 7 Uno L/R	33	2,5	296	-12	7,3	180

FLUE CONNECTION TABLE

	RECOMMENDED FLUE [mm]
	round Ø
Deko 7 Uno L/R	180



Location of the replacement air pipe
Deko 7L Uno



Location of the replacement air pipe
Deko 7R Uno

SAFETY DISTANCES TO COMBUSTIBLE MATERIALS

	CE-approval according to EN 13240				
	Behind (mm)	On the sides (mm)	In the radiation area of the door (mm)	Front (mm)	Top (mm)
Deko 7 Uno L/R	50	50	800	800	500

¹⁾ The flue calculation values apply for countries that require flue calculation in accordance with the DIN 18160 and DIN EN 13384 standards.

NOTES!

The recommended minimum flue height is 5 m. In countries where the flue calculation is required, should the calculation be done according to the instructions and regulations of the flue calculation.

A damper designed for adjusting the draft is recommended if the regional regulations permit it.

Country- and region-specific regulations must be adhered to when installing the fireplace